



Material Safety Data Sheet
Product name: Nickel–Cadmium Tel.X Battery

1. IDENTIFICATION

Product	
Product name Nickel-Cadmium battery and cell	
Trade name Tel.X Series :80, 100, 150, 180	
Supplier	
Saft America Inc. 711 Gil Harbin Industrial Blvd. Valdosta, GA 31601- USA Phone: +1 (229)-247-2331 Fax: +1 (229)-245-2890 For Chemical Emergency Spill, Leak, Fire, Exposure or Accident Call CHEMTREC - Day or night Tel: +1 (800) 424 9300	Saft Bordeaux 111/113 boulevard Alfred Daney 33074 BORDEAUX – France Phone: +33 (0)5 57 10 64 00 Fax: +33 (0)5 57 10 65 70

2. CHEMICAL COMPOSITION

Ingredients	CAS #	EINECS#	Quantity
Cadmium (as Cadmium and Cadmium hydroxide)	7440-43-9 21041-95-2	231-152-8 244-168-5	19% - 24%
Nickel (as Nickel and Nickel dihydroxide)	7440-02-0 12054-48-7	231-111-4 235-008-5	18% - 23%
Electrolyte solution (18-30% Potassium hydroxide)	1310-58-3	215-181-3	18% - 23%
Cobalt (as Cobalt hydroxide)	21041-93-0	244-166-4	2.3% - 2.9%
Plastics			10% - 12%
Steel			11% - 15%

3. HEALTH HAZARD IDENTIFICATION

Ingredients				Classification*		
Name	Chemical	CAS #	EINECS#	Symbol	Risk phrase	Safety phrase
Cadmium hydroxide	Cd(OH) ₂	21041-95-2	244-168-5	Xn N	R20/21/22 R50/53	S2, S60, S61
Nickel dihydroxide	Ni(OH) ₂	12054-48-7	235-008-5	Carc. Cat3 Xn	R40 R20/22 R43	S2, S22, S36, S60; S61
Potassium hydroxide	K(OH)	1310-58-3	215-181-3	N Xn C	R50/53 R22 R35	S ^{1/2} , S26, S36/37/39, S45
Cobalt hydroxide	Co(OH) ₂	21041-93-0	244-166-4	Xn Xi	R20/21/22 R36/R37/R38 R43	S24, S26 S36/37; S39

*Classification according to the Annex I of Directive 67/548/EEC

Effects of Overexposure	
Eye Effects	Contact with electrolyte solution contained inside battery causes very rapid, severe damage. Extremely corrosive to eye tissues. May result in permanent blindness.
Skin Effects	Contact with electrolyte solution inside battery may cause serious burns to skin tissues. Contact with nickel compounds may cause skin sensitization, resulting in chronic eczema or nickel itch.
Ingestion	Ingestion of electrolyte solution causes tissue damage to throat area and gastro/respiratory tract. Ingestion of cadmium and/or nickel compounds causes nausea and intestinal disorders.
Inhalation	Mists generated during activation procedures may cause varying degrees of irritation to the nasal mucous membranes and respiratory tract tissues varying from mild irritation of nasal mucous membranes to damage of lung tissues proper. Inhalation of cadmium compounds may cause dry throat, cough, headache, vomiting, chest pain, and/or chills. Excessive overexposure may result in pulmonary edema, breathing difficulty, and prostration.
Carcinogenicity	NIOSH recommends that nickel and cadmium be treated as occupational carcinogens.



Material Safety Data Sheet
Product name: Nickel–Cadmium Tel.X Battery

4. FIRST AID MEASURES

Battery Electrolyte	
Eye Contact	Flush with plenty of water for at least 20 minutes. Get immediate medical attention.
Skin Contact	Remove contaminated clothing and flush affected areas with plenty of water for at least 20 minutes.
Ingestion	Do not induce vomiting. Dilute by giving large volumes of water or milk. Get immediate medical attention. Do not give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air. Give oxygen or artificial respiration if needed. Get immediate medical attention.
Nickel and Cadmium Compounds	
Skin contact	Wash with cold water and soap for 15 minutes.

5. FIRE AND EXPLOSION HAZARDS

Extinguishing Media:	CO ₂ sand	
	Melting Point	Boiling Point
Cadmium	608°F / 320°C	1410°F / 766°C
Cadmium hydroxide	N/A	2838°F / 1559°C (sublimes) 4653°F / 2567°C
Copper	1981°F / 1083°C	
Nickel	2645°F / 1452°C	4950°F / 2732°C
Nickel dihydroxide	N/A	445°F / 229°C (Decomposes to NiO)
Case material : Polamyde 11	370-374°F / 188-190°C	N/A (burns may release toxic NO ₂ fumes)
Special Fire Fighting Procedures		
Use self-contained breathing apparatus to avoid breathing toxic fumes. Wear protective clothing and equipment to prevent potential body contact with electrolyte solution or mixture of water and electrolyte solution. Disconnect or cut all cables to and from battery – especially ground connection.		
Unusual Fire and Explosion Hazards		
Electrolyte solution is corrosive to all human tissues. It will react violently with many organic chemicals, especially nitrocarbons and chlorocarbons. Electrolyte solution reacts with zinc, aluminum, tin and other active materials releasing flammable hydrogen gas.		

6. ACCIDENTAL RELEASE MEASURES

Electrolyte Solution Spills	
Small (up to 19 liters / 5 gallons)	Flush with water and neutralize with dilute citric acid.
Large	Contain material in suitable containers or holding area. DO NOT allow material to enter sewers, streams, or storm conduits. Recover material with vacuum truck and dispose of properly. Reportable Quantity: 453.6 kg / 1000 pounds. 40 CFR-117.13.

7. HANDLING AND STORAGE

These cells and the batteries constructed from them may be highly charged and are capable of high energy discharge. Care should be taken to handle cells properly to avoid shorting or misuse that will result in a rapid, uncontrolled electrical, chemical, or heat energy release.

Do not transport batteries without vent caps in place.

When removing battery from service, visually inspect for leakage prior to handling. If leakage has occurred follow Spill Management Procedures.

Store in sealed packaging and in normal vertical position at temperature +20°C (68°F) ± 15°C (± 27°F) and humidity inferior at 47%.

Keep away from exposed flames, sparks, and other ignition sources.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure control			
Ingredients	CAS #	EINECS#	Exposures Limits
Cadmium (as Cadmium and Cadmium hydroxide)	7440-43-9 21041-95-2	231-152-8 244-168-5	5.0 mcg/m ³ dust – OSHA 0.05 mg/m ³ ACGIH CEILING-Fume
Nickel (as Nickel and Nickel dihydroxide)	7440-02-0 12054-48-7	231-111-4 235-008-5	1 mg/m ³ – OSHA
Electrolyte solution (18-30% Potassium hydroxide)	1310-58-3	215-181-3	2 mg/m ³ ACGIH CEILING-Air
Cobalt (as Cobalt hydroxide)	21041-93-0	244-166-4	0.1 mg/m ³ OSHA
Copper	7440-50-8	231-159-6	1 mg/ m ³ dust – OSHA



Material Safety Data Sheet

Product name: Nickel–Cadmium Tel.X Battery

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION (continued)

Personal protection

Perform battery charging procedures in a well-ventilated area. Battery operating areas must be well ventilated for the removal of potentially dangerous and harmful gases generated. Normal reactions inside the battery liberate explosive and flammable hydrogen gas

Respiratory Protection

Use NIOSH approved mist respirator during activation and actual usage to maintain exposure levels below the TWA.

Eye Protection

Use splash goggles or face shield whenever handling a battery

Hand Protection

If exposure to electrolyte solution or dried salts is likely, use any water-insoluble, non-permeable glove, i.e., synthetic rubber. DO NOT use leather or fabric gloves.

Other protective equipment

Rubber apron or rainwear, or equivalent if exposure to electrolyte solution is likely

9. PHYSICAL PROPERTIES

Boiling Point:	Not Applicable	Melting Point:	Not applicable
Vapor Pressure:	2 mm Hg at 68°F / 20°C	Vapor Density:	Not applicable
Specific Gravity:	1.17 - 1.30 (electrolyte)	Evaporation Rate:	Not Determined
Solubility in water:	Electrolyte solution is completely soluble.	Remainder:	is insoluble

10. STABILITY AND REACTIVITY

CAUTION: NEVER ACTIVATE OR TOP OFF WITH ACID

Incompatibilities

Aluminum, zinc, tin and other active metals, acid, chlorinated and aromatic hydrocarbons, nitrocarbons, halocarbons. Trichlorethylene will react with electrolyte solution to form dichloroacetylene which is spontaneously combustible.

Hazardous Decomposition Products

Nickel compounds, cadmium compounds, and potassium hydroxide.

Note that normal reactions inside battery liberate explosive and flammable hydrogen gas. Do not seal battery from atmosphere. Hazardous Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Ingredients	CAS #	EINECS#	LD ₅₀ (Oral, Rat)
Cadmium hydroxide	21041-95-2	244-168-5	225 mg/kg (Cadmium)
Nickel hydroxide	12054-48-7	235-008-5	1600 mg/kg
Potassium hydroxide	1310-58-3	215-181-3	273 mg/kg
Cobalt hydroxide	21041-93-0	244-166-4	6170 mg/kg (Cobalt)

12. ECOLOGICAL INFORMATION

The electrolyte solution (18-30% Potassium Hydroxide) is very toxic to aquatic organisms. It may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

Nickel-Cadmium batteries are universal wastes under RCRA. They may be returned to Saft Valdosta or local collecting points mentioned in Saft website (www.saftbatteries.com) for recycling.

These batteries are TCLP Toxic. These batteries and the electrolyte solution they contain are considered to be corrosives. If not recycled, they must be disposed of in accordance with all federal, state, and local hazardous waste regulations.

14. TRANSPORTATION INFORMATION

Batteries being forwarded or being returned to Saft for repair should be shipped as Hazardous Material using the following description:

[Batteries, Wet, Filled with Alkali, 8, UN2795, PG III.](#)

Spent batteries being sent to Saft Valdosta or local collecting points for recycling should be shipped as Universal Waste using the following description:

[Used Batteries, Wet, Filled with Alkali, 8, UN2795, PG III.](#)

15. REGULATIONS

EPCRA reporting requirements

Section 313 Supplier Notification – This product contains the following EPCRA Section 313 chemicals subject to the reporting requirements of Section 313 if the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):

CAS #	EINECS#	Chemical Name	Percent by Weight
7440-43-9	231-152-8	Cadmium	22 %
7440-48-4	231-158-0	Cobalt	2.6%
7440-02-0	231-111-4	Nickel	21 %

A copy of this MSDS may be required to be filled with your local emergency planning commission, state emergency response



Material Safety Data Sheet
Product name: Nickel–Cadmium Tel.X Battery

EPCRA reporting requirements (continued)

commission, and local fire department in accordance with sections of the Emergency Planning and Community right-To-Know Act.

EC classification

Symbols

C	Corrosive
N	Dangerous for the environment
Xn	Harmful
Xi	Irritant

Risk phrases

R20	Harmful by inhalation
R21	Harmful in contact with skin
R22	Harmful if swallowed
R36	Irritating to eyes
R37	Irritating to respiratory system
R38	Irritating to skin
R40	Limited evidence of a carcinogenic effect
R41	Risk of serious damage to the eyes
R43	May cause sensitization by skin contact
R50/53	Very Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases

S1/2	Keep locked up and out of the reach of children
S2	Keep out of the reach of children
S20	When using, do not eat or drink
S22	Do not breathe dust
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S36	Wear suitable protective clothing
S37	Wear suitable gloves
S39	Wear eyes/face protection
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible.)
S60	Must be disposed of as hazardous waste.
S61	Avoid release to the environment

16. OTHER INFORMATION

HMIS Ratings

Health	3
Flammability	0
Reactivity	1

NFPA Ratings

Health	3
Flammability	0
Reactivity	1

Disclaimer : This information has been compiled for sources considered to be dependable and is, to the best of our knowledge and belief, accurate and reliable as of the dated compiled. However, no representation, warranty (either expressed or implied) or guarantee is made to the accuracy, reliability or completeness of the information contained herein. This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his own particular use. We do not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information nor do we offer warranty against patent infringement. Additional information is available by calling the telephone number above designated for this purpose.